

Klarwasserdruckpumpe GAP X120

clarified water pressure pump GAP X120



Technisches Datenblatt / technical data

Pumpe		pump	
max. Förderleistung	100 l/min	max. flowrate	
max. Förderhöhe	45 m	max. height	
max. Betriebsdruck	4,5 bar	max. operating pressure	
Nennleistung max.	1,15 kW	power consumption	
max. Arbeitsdruck		max. working pressure	
max. Temperatur des geförderten Mediums	35 °C	max. temperature of pumped liquid	
Pumpenlaufräder (Material)	Siliziumstahlbleche / silicon steel sheet	rotor discs of the pump (material)	
Pumpenschaft (Material)	Edelstahl / stainless steel	shaft of the pump (material)	
Pumpengehäuse (Material)	PP-GF Edelstahl / PP-GF stainless steel	pump body housing (material)	

Anschlüsse		connections	
Saugseite	1" AG / male thread	suction side	
Druckleitung	1" IG / female thread	pressure side	

Netzanschluss		electric main supply	
Spannung	230 V	voltage	
Frequenz	50 Hz	frequency	
Kabellänge	15 m	length of cable	

Abmessungen		measurements	
Durchmesser	150 mm	diameter	
Höhe	535 mm	height	
Gewicht	10,7 kg	weight	

